

8-channel Compact Mixer PLAYMIX8-JP

PLAYMIXは、コンパクトでスタイリッシュなパッケージの中に、充実した機能、優れたオーディオクオリティを備えたコンパクトミキシングコンソールです。

PLAYMIXには、チャンネルとマスターの機能は同じで、6、8、10入力の3モデルが用意されています。モノラルのMIC/LINEチャンネルには、低ノイズ、高ヘッドルームのマイクプリアンプ、スイープMIDとHPFを備えた3バンドEQ、60mmのコントロールフェーダーが搭載され、サウンドを完全にコントロールすることができます。

全モデルに、LCDディスプレイを搭載し、先進のDIGITALセクションを搭載しています。

- 4モノインプット+2ステレオインプット / メイン出力 (XLR L・R)、コントロールルーム出力 (フォーン L・R)、ヘッドホン、AUX出力
- 高品質な24-bit DSPを内蔵し、単体および複合エフェクト (REVERBS、DELAYS、MODULATIONS) のスタジオグレードのプリセットを100種類搭載
- PC接続による再生・録音が可能な48KHzステレオUSBオーディオインターフェース機能
- MP3プレーヤー搭載。USBメモリーまたはBluetooth接続デバイスの再生が可能
- MP3レコーダー搭載。USBメモリーへのステレオ録音が可能。

主な仕様

MONO INPUT CHANNEL

Mic Input	sensitivity	from -10 to -45 dB	Balanced XLR-F
	impedance	1 KΩ	
Line Input	sensitivity	from +20 to -15 dB	Balanced JACK
	impedance	20 KΩ	
Lo cut		80Hz, 6dB/oct.	
EQ	HIGH (shelving)	±15 dB @ 12KHz	
	MID (peaking)	±12 dB @ 250-6KHz	
	LOW (shelving)	±15 dB @ 80 Hz	

STEREO INPUT CHANNEL

Line Input	sensitivity	from +12 to -15 dB	Balanced JACK
	impedance	20KΩ	Stereo Mini JACK

MASTER SECTION

MAIN MIX	nom. out level	+4 dBu	Unbalanced XLR-M
C. ROOM output	nom. out level	+4 dBu	Unbalanced JACK
SEND output	nom. out level	+4 dBu	Unbalanced JACK
HEADPHONES	min. impedance	64 ohm	Stereo JACK
Bluetooth		Version 5.0, Audio Streaming	
USB Audio Interface (Type A)		Stereo IN/OUT, 16-bit converter / 44.1 KHz (PENDING) / 48 KHz (PC) sample rate	

DIGITAL EFFECT PROCESSOR

Effects	100 presets
A/D and D/A converters	24 bit
DSP resolution	24 bit
Controls	2-DIGIT displav. DIAL. LEVEL

GENERAL SPECIFICATIONS

Maximum level	all outputs	+15 dBu
Crosstalk meas. at 1 KHz		> 75 dB
HUM & Noise	unweighted	< 90 dB
THD + Noise	at +4dB, 1kHz	< 0,009 %
Dimensions (WxHxD)		331 x 274 x 61 mm
Weight		2,50 kg

POWER REQUIREMENTS

Supply	use only supplied AC/DC ADAPTER 5VDC 2A
--------	---

外観寸法図

